




DISTILLED TURPENTINE

Mixtures of bicyclic monoterpene hydrocarbons



SPECIFICATIONS	Appearance	Clear liquid
	Colour, Hazen Unit (HU)	100
	maximum	0.8600 - 0.8700
	Specific Gravity @ 20° C	Nil
	Ash Content	
TYPICAL PROPERTIES	Refractive index @ 20°C	1.4700 – 1.4800
	Distillation Range : Initial	165° C
	95 ml	215° C
	Flash Point (TCC)	above 35°C
	Odour	Terpenic
REGULATORY/ CLASSIFICATIONS	CAS No.	8006-24-2
	Shipping Name	Distilled Turpentine
	UN	N.A
TOXICOLOGY INFORMATION	LD50 Oral (rat)	N.A
	LD50 Dermal (rabbit)	N.A.
	Skin Irritation (20% in petrolatum)	No irritation
	Skin sensitization (20% in petrolatum)	No sensitization.
	Undiluted liquid may cause skin and eye irritation	
SHIPPING INFORMATION	Weight / Litre	0.865 Kg (20°C)
	Containers	175 kgs. Metal drum Net wt.
	Factory	Bareilly(U.P)
	Shipping Point	Mumbai. Nhava Sheva(India)

APPLICATIONS:

- In resins, lacquers, waxes, alkyd resins, rosins, printing inks, belt dressings & polishes as an excellent solvent.
- In paints, varnishes, oils & enamels, as a thinner.
- In preparation of mild fumigant, formulations, disinfectants & insecticides.

IMPORTANT

The data submitted above is for guidance only. Since many factors affect the processing & application of our product, processors should carry out their own tests before any particular application. Therefore, no warranty is expressed or implied in this sale. Relevant patents & Government regulations must be respected.